

Some potentially useful formulas

$$F = \frac{G m_1 m_2}{r^2}$$

$$F = \frac{k q_1 q_2}{r^2}$$

$$F = ma$$

$$(\text{distance}) = (\text{Speed})(\text{time})$$

$$v = \frac{\Delta x}{\Delta t}$$

$$a = \frac{\Delta v}{\Delta t}$$

$$\text{Work} = \text{force} \times \text{distance}$$

$$\text{Momentum} = p = mv$$

$$\Delta x' = \gamma \Delta x, \Delta x \text{ longest in proper frame}$$

$$\Delta t' = \gamma \Delta t, \Delta t \text{ shortest in proper frame}$$

$$\gamma = \frac{1}{\sqrt{1 - \left(\frac{v}{c}\right)^2}}$$

$$c = 3 \times 10^8 \text{ m/s}$$

$$h = 6.6 \times 10^{-34} \text{ J}\cdot\text{s}$$

$$\lambda = \frac{h}{p} = \frac{h}{mv}$$

$$v = \lambda \nu$$

$$\nu = \frac{1}{T} \quad (T = \text{period})$$

$$\Delta x \Delta p > h \quad \Delta E \Delta t > h$$

$$E = h\nu$$

$$\frac{\Delta N}{\Delta t} = \lambda N$$

$$t_{1/2} = \frac{0.693}{\lambda}$$